

Product Portfolio

2005



PULS supplies consistently reliable and technologically superior power supplies.

PULS is always nearby and there for you.

www.pulspower.com

DIMENSION Q-Series

- Unparalleled compact design, up to 55% less space required
- Unmatched efficiency of up to 95%
- MTBF > 600 000h, specified capacitor lifetime > 50 000h
- 80W to 480W output power
- 1-phase or 3-phase input
- Metal housing
- Quick-connect spring-clamp terminals
- Output voltages from 12V to 56V
- 150% peak load capability up to +60°C
- DC-OK relay contact
- Operation from -25°C to +60°C
- Active PFC, even for 3-phase input
- 85V to 264V_{ac} wide-range input (single phase)
- DC input from 88V to 370V_{dc} (single phase)
- Extra low inrush current
- Ride through buffer units
- Decoupling modules

SL product family

- 40W to 960W output
- 1-phase or 3-phase input
- DC/DC-Converter
- Metal housing
- Screw terminals or plug connector (SLR)
- Output voltages from 5V to 56V
- Up to 25% Power Boost
- Selector for parallel operation with load sharing
- Redundancy units and decoupling modules
- AS-interface power supplies
- Buffer unit
- Largest product range

ML-product family

- 25W to 100W output
- 1-phase input
- Molded plastic housing
- Quick-connect spring-clamp terminals
- Output voltages from 5V to 56V
- Special measures for parallel operation
- Decoupling module for redundancy

Product Portfolio 2005

		25-40W	50-60W	72-85W	90-100W	120W	180-240W	480W	720W	960W	>960W
1-phase	5V	ML30.101									Parallel two or more units
	10-12V	ML30.102									
	12-15V	SL2.103	ML50.102		ML100.102	SL10.104	QS10.121*				
	±12-15V	ML30.106									
	24-28V	ML30.100	ML50.100 ML50.101 ML50.111 SL2.100 SLR2.100 ¹⁾	QS3.241* ML70.100	SL4.100 ML95.100 ML100.100	QS5.241* SL5.100 SL5.102 SL5.105 SLR5.100 ¹⁾	QS10.241* SL10.100 SL10.105 SLR10.100 ¹⁾	SL20.100 SL20.101 SL20.110 SL20.111 SL20.115	SL30.100		
	28-32V						QS10.301*				
	36-43V							SL20.112			
	48-56V		ML50.105		ML100.105		QS10.481* SL10.101 SL10.106	SL20.113			
3-phase	24-28V				ML100.200*	SL5.300	SL10.300	QT20.241* SL20.300 SL20.301 SL20.310	SL30.300	SL40.300 SL40.301	
	36-43V							QT20.361*			
	48-56V						SL10.305*	QT20.481* SL20.303			
DC/DC	DC/DC converter	SLD2.100									
	AS-interface			SLA3.100		SLA4.100	SLA8.100 SLA8.300				
	DeviceNet®				QS5.DNET*		QS10.DNET*				
	Redundancy Mod.	SLR02							SLR01		
	Decoupling Mod.	MLY02.100					YR2.Diode*				
	Buffer Unit	SLV20.200	UF20.241*(24V)		UF20.481*(48V)						

1) Redundancy option included

*New

Detailed product specifications are available on our website along with datasheets, technical notes, reports and applications. Our sales staff will be pleased to provide expert advice and assistance.

Germany PULS in München, Tel. +49 89 9278 0
China PULS in Shanghai, Tel. +86 21 6432 7680
France PULS in Limonest/Lyon, Tél. +33 478 668 941
North America PULS in St. Charles/Chicago, Tel. +1 630 587 9780
Austria PULS in Rohrbach, Tel. +43 2764 32 13
Switzerland PULS in Oberflachs/Aargau, Tel. +41 56 450 18 10
United Kingdom PULS in Bedfordshire, Tel. +44 1525 720099

www.pulspower.com
www.puls-power.cn
www.puls-power.com/fr
www.puls-power.us
www.pulspower.com
www.puls-power.ch
www.puls.co.uk

www.pulspower.com